



GENERAL
PURPOSE



EN16350



EN388



4131A

EN407



X1XXXX



CUT



ATTRIBUTES:

- 18 gauge grey Kyorene® graphene ESD liner
- Black HCT® nano-foam nitrile palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Assembly of small pieces
- General handling
- Packaging
- Mounting and dismantling
- Machine tool operation
- Quality inspection
- Applications requiring dexterity and precision
- Compatible with consumer & industrial touchscreen
- Environments requiring ESD protection
- Warehouse and logistic operations

CATEGORY:

- **Kyorene®**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



Oeko-Tex®
Standard 100



PACKAGING:

| GLOVE SIZE | 6 | 7 | 8 | 9 | 10 | 11 |
|------------|--------|-----|--------|-------|-------|------|
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE | 72 | 72 | 72 | 72 | 72 | 72 |

PERFORMANCE LEVEL:

EN388: 4131A

| ABRASION | | 1 | 2 | 3 | 4 | |
|--------------|---|---|---|---|---|---|
| CUT | | 1 | 2 | 3 | 4 | 5 |
| TEAR | | 1 | 2 | 3 | 4 | |
| PUNCTURE | | 1 | 2 | 3 | 4 | |
| CUT TDM TEST | A | B | C | D | E | F |



VERIFIED GRAPHENE®
PRODUCER
THE GRAPHENE COUNCIL

