

00 - 839VC









FN388















ϵ

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4X32E

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	Α	В	С	D	Е	F

VERIFIED GRAPHENE

ATTRIBUTES:

- · 18G graphene Ultra High Molecular Weight Polyethylene liner with acrylic lining
- · Black HCT® micro foam Nitrile Palm coating

FEATURES:

- · No stainless steel or fiberglass
- · Ergonomically shaped for superior fit
- · Bacteriostatic kills harmful bacteria
- · Thermal regulating to keep the hands comfortable
- · Odor neutralizing to keep the gloves smelling fresh
 - · DMF and silicone free

APPLICATIONS:

- · Forklift drivers
- Carpentry
- · Handling glass and windows
- · Handling heavy equipment

CATEGORY:

· Kyorene® Pro

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

