



EN511



X2X

EN407



X2XXXX

EN388



4X43FP



CUT



Oeko-Tex<sup>®</sup>  
Standard 100



## ATTRIBUTES:

- 18 gauge grey Kyorene<sup>®</sup> Pro graphene liner & 7g poly-acrylic lining
- Black HCT<sup>®</sup> microfoam nitrile palm coating

## FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

## APPLICATIONS:

- Maintenance refineries and ports
- Transport logistics
- Heavy parts handling
- Construction
- Off-shore drilling

## CATEGORY:

- **Kyorene<sup>®</sup> Pro**

## CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

## TECHNOLOGIES:

## PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	24	24	24	24	24	24

## PERFORMANCE LEVEL:

EN388: 4X43FP

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT		F			P	

