



GENERAL
PURPOSE



EN388



4121A

EN407



X1XXXX



CUT



Oeko-Tex®
Standard 100



ATTRIBUTES:

- 15 gauge grey Kyorene® graphene liner
- HCT® micro foam nitrile coating with dotted palm

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Automotive manufacturing
- Light manufacturing
- Maintenance
- Warehousing
- Landscaping

CATEGORY:

- **Kyorene®**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

PACKAGING:

| GLOVE SIZE | 6 | 7 | 8 | 9 | 10 | 11 |
|------------|--------|-----|--------|-------|-------|------|
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE | 72 | 72 | 72 | 72 | 72 | 72 |

PERFORMANCE LEVEL:

EN388: 4121A

| ABRASION | | 1 | 2 | 3 | 4 | |
|--------------|---|---|---|---|---|---|
| CUT | | 1 | 2 | 3 | 4 | 5 |
| TEAR | | 1 | 2 | 3 | 4 | |
| PUNCTURE | | 1 | 2 | 3 | 4 | |
| CUT TDM TEST | A | B | C | D | E | F |

