



GENERAL  
PURPOSE



EN388



4121A

EN407



X1XXXX



CUT



### ATTRIBUTES:

- 15 gauge Kyorene® graphene liner
- HCT® micro foam nitrile knuckle coating with dotted palm

### FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Automotive manufacturing
- Light manufacturing
- Maintenance
- Warehousing
- Landscaping



Oeko-Tex®  
Standard 100



### PACKAGING:

<b>GLOVE SIZE</b>	6	7	8	9	10	11
<b>CUFF COLOR</b>	Purple	Red	Yellow	Brown	Black	Blue
<b>PER CASE</b>	72	72	72	72	72	72

### CATEGORY:

- **Kyorene®**

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

### PERFORMANCE LEVEL:

EN388: 4121A

<b>ABRASION</b>		1	2	3	4	
<b>CUT</b>		1	2	3	4	5
<b>TEAR</b>		1	2	3	4	
<b>PUNCTURE</b>		1	2	3	4	
<b>CUT TDM TEST</b>	A	B	C	D	E	F

