



GENERAL  
PURPOSE



EN388



4121A

EN407



X1XXXX



CUT



Oeko-Tex®  
Standard 100



## ATTRIBUTES:

- 15 gauge Kyorene® graphene liner
- With Blue Nitrile HCT® micro foam, Knuckle Coating

## FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

## APPLICATIONS:

- Automotive manufacturing
- Light manufacturing
- Maintenance
- Warehousing
- Landscaping

## CATEGORY:

- **Kyorene®**

## CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

## TECHNOLOGIES:

## PACKAGING:

| GLOVE SIZE | 6      | 7   | 8      | 9     | 10    | 11   |
|------------|--------|-----|--------|-------|-------|------|
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE   | 72     | 72  | 72     | 72    | 72    | 72   |

## PERFORMANCE LEVEL:

EN388: 4121A

| ABRASION     |   | 1 | 2 | 3 | 4 |   |
|--------------|---|---|---|---|---|---|
| CUT          |   | 1 | 2 | 3 | 4 | 5 |
| TEAR         |   | 1 | 2 | 3 | 4 |   |
| PUNCTURE     |   | 1 | 2 | 3 | 4 |   |
| CUT TDM TEST | A | B | C | D | E | F |



VERIFIED GRAPHENE®  
PRODUCER  
THE GRAPHENE COUNCIL

