



GENERAL  
PURPOSE



EN388



4121A

EN407



X1XXXX



CUT



Oeko-Tex®  
Standard 100



## ATTRIBUTES:

- 15 gauge grey Kyorene® graphene liner
- Full blue nitrile coating with black HCT® micro foam nitrile palm coating for superior oil and water resistance

## FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

## APPLICATIONS:

- Aerospace
- Automotive manufacturing
- Maintenance

## CATEGORY:

- **Kyorene®**

## CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

## TECHNOLOGIES:

## PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

## PERFORMANCE LEVEL:

EN388: 4121A

ABRASION		1	2	3	4	
CUT		1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F



**VERIFIED GRAPHENE®**  
PRODUCER  
THE GRAPHENE COUNCIL

