



EN388



4X42B



CUT



Oeko-Tex®  
Standard 100



### ATTRIBUTES:

- 13 gauge grey Kyorene® graphene liner
- Black HCT® Nano-foam nitrile palm coating

### FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Automotive
- Auto Aftermarket
- Machinery and Equipment
- Oil and Gas
- Utility & Public Works
- Warehousing & Logistics

### CATEGORY:

- **Kyorene®**

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

### PACKAGING:

| GLOVE SIZE | 6      | 7   | 8      | 9     | 10    | 11   |
|------------|--------|-----|--------|-------|-------|------|
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE   | 72     | 72  | 72     | 72    | 72    | 72   |

### PERFORMANCE LEVEL:

EN388: 4X42B

|              |   |   |   |   |   |   |
|--------------|---|---|---|---|---|---|
| ABRASION     |   | 1 | 2 | 3 | 4 |   |
| CUT          | X | 1 | 2 | 3 | 4 | 5 |
| TEAR         |   | 1 | 2 | 3 | 4 |   |
| PUNCTURE     |   | 1 | 2 | 3 | 4 |   |
| CUT TDM TEST | A | B | C | D | E | F |



**VERIFIED GRAPHENE®**  
PRODUCER  
THE GRAPHENE COUNCIL



Hybrid Coating Technology