



**KYORENE®**  
THE GRAPHENE FIBER

**02 - 405R**

SPECIFICATION SHEET



EN388



4X42D



CUT



Oeko-Tex®  
Standard 100



## ATTRIBUTES:

- 13 gauge grey Kyorene® graphene liner
- Black HCT® micro foam nitrile palm coating

## FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

## APPLICATIONS:

- Automotive manufacturing
- Appliance manufacturing
- Metal stamping
- Sheet metal handling
- Construction
- Extruded plastics

## CATEGORY:

- **Kyorene®**

## CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

## TECHNOLOGIES:

## PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

## PERFORMANCE LEVEL:

EN388: 4X42D

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F

