



KYORENE®
THE GRAPHENE FIBER

04 - 205R

SPECIFICATION SHEET



EN388



4X42B



CUT



Oeko-Tex®
Standard 100



ATTRIBUTES:

- 13 gauge grey Kyorene® graphene liner
- Polyurethane palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Automotive
- Auto Aftermarket
- Machinery and Equipment
- Oil and Gas
- Utility & Public Works
- Warehousing & Logistic

CATEGORY:

- **Kyorene®**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4X42B

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F



VERIFIED GRAPHENE®
PRODUCER
THE GRAPHENE COUNCIL



Hybrid Coating Technology