



KYORENE®
THE GRAPHENE FIBER

09 - 605R1

SPECIFICATION SHEET



EN388



4X42F

EN407



X1XXXX



CUT



ATTRIBUTES:

- 13 gauge grey Kyorene® graphene liner
- Black Crinkle Latex palm coating

FEATURES:

- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Bottling
- Glass handling
- Heavy material handling



Oeko-Tex®
Standard 100



TOUCH
SCREEN

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

CATEGORY:

- Kyorene®

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

PERFORMANCE LEVEL:

EN388: 4X42F

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F



VERIFIED GRAPHENE®
PRODUCER
THE GRAPHENE COUNCIL



Hybrid Coating Technology