



EN388



2X4XF



CUT



Oeko-Tex<sup>®</sup>  
Standard 100



### ATTRIBUTES:

- 45cm, 13 gauge grey Kyorene<sup>®</sup> Pro graphene sleeve

### FEATURES:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Metal fabrication
- Metal stamping
- Steel processing
- Glass handling

### CATEGORY:

- **Kyorene<sup>®</sup> Pro**

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

### PACKAGING:

GLOVE SIZE	One size
PER CASE	144

### PERFORMANCE LEVEL:

EN388: 2X4XF

ABRASION		1	2	3	4	5
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	5
PUNCTURE	X	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F

