



EN407



X1XXXX

EN388



4X43FP



CUT



Oeko-Tex[®]
Standard 100



ATTRIBUTES:

- 18 gauge grey Kyorene[®] Pro graphene liner
- Black HCT[®] micro foam nitrile palm coating

FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

APPLICATIONS:

- Oil & gas
- Mining
- Construction

CATEGORY:

- **Kyorene[®] Pro**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

PERFORMANCE LEVEL:

EN388: 4X43FP

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F
IMPACT		F		P		

