



EN388



4X43F



CUT



Oeko-Tex<sup>®</sup>  
Standard 100



### ATTRIBUTES:

- 18 gauge grey Kyorene<sup>®</sup> Pro graphene liner
- Black HCT<sup>®</sup> micro foam nitrile palm coating

### FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Metal fabrication
- Steel processing
- Recycling
- Glass manufacturing

### CATEGORY:

- **Kyorene<sup>®</sup> Pro**

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

### PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	72	72	72	72	72	72

### PERFORMANCE LEVEL:

EN388: 4X43F

ABRASION		1	2	3	4	
CUT	X	1	2	3	4	5
TEAR		1	2	3	4	
PUNCTURE		1	2	3	4	
CUT TDM TEST	A	B	C	D	E	F

