# KYORENE®

# KO2 - 303L

SPECIFICATION SHEET











EN388











### **PACKAGING:**

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue

#### **PERFORMANCE LEVEL:**

EN388: 4X31C

ABRASION		1	2	3	4	5
CUT	Χ	1	2	3	4	5
TEAR		1	2	3	4	5
PUNCTURE		1	2	3	4	5
CUT TDM TEST	Α	В	С	D	Е	F



#### **ATTRIBUTES:**

- 18 gauge 100D grey Kyorene® Pro graphene liner
- · Black HCT® Nano-foam palm coating

### **FEATURES:**

- · No stainless steel or fiberglass
- · Ergonomically shaped for superior fit
- · Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- · Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

## **APPLICATIONS:**

- Automotive manufacturing
- · Metal stamping
- · Sheet metal handling
- · Steel processing
- Construction

#### **CATEGORY:**

· Kyorene® Pro

#### **CARE INSTRUCTIONS:**

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

#### **TECHNOLOGIES:**

