



EN388



4X42D



CUT



Oeko-Tex<sup>®</sup>  
Standard 100



### ATTRIBUTES:

- 18 gauge grey Kyorene<sup>®</sup> Pro graphene liner
- Black polyurethane palm coating

### FEATURES:

- No stainless steel or fiberglass
- Ergonomically shaped for superior fit
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- DMF and silicone free

### APPLICATIONS:

- Oil & gas
- Mining
- Construction

### CATEGORY:

- **Kyorene<sup>®</sup> Pro**

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

### PACKAGING:

| GLOVE SIZE | 6      | 7   | 8      | 9     | 10    | 11   |
|------------|--------|-----|--------|-------|-------|------|
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE   | 72     | 72  | 72     | 72    | 72    | 72   |

### PERFORMANCE LEVEL:

EN388: 4X42D

|              |   |   |   |   |   |   |
|--------------|---|---|---|---|---|---|
| ABRASION     |   | 1 | 2 | 3 | 4 | 5 |
| CUT          | X | 1 | 2 | 3 | 4 | 5 |
| TEAR         |   | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE     |   | 1 | 2 | 3 | 4 | 5 |
| CUT TDM TEST | A | B | C | D | E | F |



VERIFIED GRAPHENE<sup>®</sup>  
PRODUCER  
THE GRAPHENE COUNCIL

